

TM BATTERIES TM BATTERIES LTD.

Top Matching Cell Solution

Building 18, Tongfuyu Industrial Park, Longhua New District, Shenzhen, Guangdong, China

Tel: (+86)-755 2917 9250

Fax: (+86)-755 2917 9251

Website: www.tmbatteries.com

Email: info@tmbatteries.com

High Drain Lithium Polymer (Lipo) Conventional Cell List

Capacity (mAh)	C Rate	Dimension (mm) (Thickness*Width*Length)	Approx. Weight (gram)
1000	10C	6.5*34*65	27
1000	20C	6.4*34*65	28
1000	25C	6.2*34*65	26
1300	20C	7.7*34*65	33
1300	25C	7.3*34*65	32
1300	30C	7.7*34*65	33
1300	35C	7.9*34*65	35
2200	20C	7.5*34*97	52
1500	25C	5.4*34*97	38
1800	25C	6.5*34*97	43
2000	25C	7.2*34*97	49
2200	25C	7.7*34*97	53
2400	25C	8.0*34*97	56
2200	30C	7.8*34*97	54
2200	35C	8.0*34*97	56
1800	40C	6.9*34*97	45
2200	40C	8.0*34*97	55
2600	50C	8.5*34*97	57
800	15C	7.6*30*49	23
1000	15C	9.2*30*49	27
500	25C	5.0*30*49	13
800	25C	7.2*30*49	20
350	30C	3.5*30*49	10
350	35C	3.7*30*49	11
360	25C	3.6*30*49	10.5
450	25C	4.8*30*49	12.8
850	25C	7.3*30*49	21
2600	25C	5.1*46*133	63
4400	30C	7.7*46*133	105
5000	30C	8.5*46*133	117
4400	35C	7.9*46*133	107
5000	35C	8.7*46*133	119
2500	25C	5.0*43*128	62
3700	25C	7.1*43*128	85
4500	25C	8.5*43*128	110
5000	25C	10.0*43*128	120
6000	25C	10.7*43*128	138
2800	25C	5.5*43*128	67
3300	25C	6.5*43*128	78
4000	25C	7.8*43*128	95
2800	30C	5.7*43*128	70

Capacity (mAh)	C Rate	Dimension (mm) (Thickness*Width*Length)	Approx. Weight (gram)
3300	30C	6.6*43*128	80
4000	30C	7.9*43*128	98
5000	30C	10.2*43*128	124
2800	35C	5.9*43*128	73
3300	35C	6.8*43*128	82
4000	35C	8.1*43*128	100
5000	35C	10.4*43*128	126
3300	40C	6.9*43*128	84
4000	40C	8.0*43*128	100
5000	40C	11.0*43*128	128
5200	50C	11.3*43*128	135
6000	50C	11.7*43*128	145
8000	30C	6.5*53*180	180