

**NiMH Conventional Cell List for RC Hobby Batteries**

TM Model No.	Height*Dia. (mm)	Nominal Capacity (mAh)	Nominal Voltage (V)	10C Discharge Time (min.)	10C Discharge Average Volts	IR (m Ω)	Approx. Weight(g)
TM 2/3A1200	28.5*17	1200	1.2	5.0~6.0	1.13	12	22
TM 2/3A1300	28.5*17	1300	1.2	5.0~6.0	1.09	15	21
TM 2/3A1500	28.5*17	1500	1.2	5.0~6.0	1.13	10	23
TM 2/3A1600	28.5*17	1600	1.2	5.0~6.0	1.17	10	23
TM 4/5AA2000	42.5*17	2000	1.2	5.0~6.0	1.11	8.5	31
TM AA1600	50.5*14.3	1600	1.2	5.0~6.0	1.14	12	28.5
TM SC1700	43*22.3	1700	1.2	5.0~6.0	1.11	8	40
TM SC2000	43*22.3	2000	1.2	5.0~6.0	1.11	8	41
TM SC2200	43*22.3	2200	1.2	5.0~6.0	1.11	8	42
TM 4/5SC2200	33.5*22.3	2200	1.2	5.0~6.0	1.11	6.5	41
TM SC2400	43*22.3	2400	1.2	5.0~6.0	1.12	7	46
TM SC2750	43*22.3	2750	1.2	5.0~6.0	1.12	7	49
TM SC3000	43*22.3	3000	1.2	5.0~6.0	1.12	6	53
TM SC3300	43*22.3	3300	1.2	6.0~6.6	1.12	6	56
TM SC3500	43*22.3	3500	1.2	6.6~7.0	1.13	5.5	58
TM SC3600	43*22.3	3600	1.2	6.8~7.2	1.13	5.5	59
TM SC3800	43*22.3	3800	1.2	7.2~7.6	1.14	4.5	62
TM SC4000	43.5*23	4000	1.2	7.6~8.0	1.14	4.5	64
TM SC4200	43.5*23	4200	1.2	8.4	1.235	3	69
TM SC4500	43.5*23	4500	1.2	9	1.24	2.5	70.5
TM SC4600	43.5*23	4600	1.2	9.2	1.24	1.5	71.5
TM SC5000	43.5*23	5000	1.2	9.9	1.19	2.5	72