

**Typical Lipo Power Pack for Competition Racing**

TM Cell Model	Capacity (mAh)	Volts	Approx. Dimensions (mm)			Pack IR (mΩ)	Approx. Weight (g)	Max Discharge Current	
			Thickness	Width	Length			Continuous	Burst
753496	1800	7.4	16	35	103.5	10	113.0	65C	130C
753496	1800	11.1	23.4	35	103.5	13	164.5	65C	130C
753496	1800	14.8	30.8	35	104.5	16	215.0	65C	130C
753496	1800	18.5	38.3	35	104.5	19	266.0	65C	130C
753496	1800	22.2	45.8	35	104.5	22	317.0	65C	130C
903496	2250	7.4	19	35	103.5	10	135.2	65C	130C
903496	2250	11.1	28	35	103.5	13	197.4	65C	130C
903496	2250	14.8	37	35	104.5	16	258.9	65C	130C
903496	2250	18.5	46.1	35	104.5	19	321.4	65C	130C
903496	2250	22.2	55.2	35	104.5	22	382.9	65C	130C
6544125	2700	7.4	13.8	44	133	8	174.0	65C	130C
6544125	2700	11.1	20.2	44	133	10	251.0	65C	130C
6544125	2700	14.8	26.6	44	133	12	325.0	65C	130C
6544125	2700	18.5	33.1	44	134	14	402.0	65C	130C
6544125	2700	22.2	39.6	44	134	16	476.0	65C	130C
8044125	3300	7.4	16.6	44	133	8	205.0	65C	130C
8044125	3300	11.1	24.3	44	133	10	297.5	65C	130C
8044125	3300	14.8	32	44	133	12	389.0	65C	130C
8044125	3300	18.5	39.8	44	134	14	481.0	65C	130C
8044125	3300	22.2	47.6	44	134	16	570.0	65C	130C
9044125	3850	7.4	19	44	134	8	232.0	65C	130C
9044125	3850	11.1	28	44	134	10	338.0	65C	130C
9044125	3850	14.8	37	44	134	12	441.0	65C	130C
9044125	3850	18.5	46.1	44	135	14	548.0	65C	130C
9044125	3850	22.2	55.2	44	135	16	652.0	65C	130C
8048145	4400	7.4	17	49	154	8	262.5	65C	130C
8048145	4400	11.1	24.9	49	154	10	383.0	65C	130C
8048145	4400	14.8	32.8	49	154	12	501.0	65C	130C
8048145	4400	18.5	40.8	49	155	14	623.0	65C	130C
8048145	4400	22.2	48.8	49	155	16	741.0	65C	130C
9048145	5000	7.4	18.8	49	154	8	289.0	65C	130C
9048145	5000	11.1	27.6	49	154	10	423.0	65C	130C
9048145	5000	14.8	36.4	49	154	12	554.0	65C	130C
9048145	5000	18.5	45.3	49	155	14	688.0	65C	130C
9048145	5000	22.2	54.2	49	155	16	820.0	65C	130C

TM Cell Model	Capacity (mAh)	Volts	Approx. Dimensions (mm)			Pack IR (mΩ)	Approx. Weight (g)	Max Discharge Current	
			Thickness	Width	Length			Continuous	Burst
5544125	6600	7.4	25	46.5	138	8	307.0	60C	100C
5544125	6000	7.4	25	46.5	138	8	298.0	60C	100C
554283	4200	7.4	25	46.5	95.5	13	200.0	60C	100C
744358	5000	7.4	25	46.5	69.5	8	266.0	60C	100C
784281	5600	3.7	18.5	46.5	93	8	140.0	60C	100C